




balance vanity	series#	dimensions	lampping	diffuser	finishes	options
	<b>2-5137</b>	W = 24.63" H = 2.5" E = 3.5"	1 x 24W T5HO fluorescent (mini bi-pin)	acrylic	<b>24</b> satin nickel	<b>BP224</b> backplate 26.75"(w) x 4.5"(h) 0.5"(ext from wall)
	<b>2-5138</b>	W = 36.5" H = 2.5" E = 3.5"	1 x 39W T5HO fluorescent (mini bi-pin)			<b>BP324</b> backplate 38.5"(w) x 4.5"(h) 0.5"(ext from wall)
	<b>2-5139</b>	W = 48.25" H = 2.5" E = 3.5"	1 x 54W T5HO fluorescent (mini bi-pin)			<b>BP424</b> backplate 50.38"(w) x 4.5"(h) 0.5"(ext from wall)

**general specifications**

- Cold-rolled steel housing.
- Diffusers are 1/8" thick matte white acrylic.
- All items U.L and C.U.L. approved for damp locations.
- Fluorescent ballasts are electronic, HPF program start, universal voltage (120V - 277V.)
- All units mount to 2" X 3" junction box as standard, or 4" octagonal junction box with accessory backplate.
- All units approved for horizontal mounting.
- Visit [www.oxygenlighting.com](http://www.oxygenlighting.com) for technical cut sheets.
- Oxygen lighting reserves the right to modify designs at any time.

**sample catalog number**

series #	finish	options	catalog number
<b>2-5137</b>	<b>- 24</b>	<b>- BP224</b>	<b>2-5137-24-BP224</b>
balance vanity, 24W T5HO	satin nickel	backplate	

