



| journey ceiling mounts | series# | lamping | dimensions | finishes | options |
|-------------------------------------|---------------|---|---------------------------|---|---|
| • twist fit glass diffuser | 2-6134 | 2 x 13W quad 4-pin fluorescent (G24q-1) | W = 11" dia. H = 3.5" | 24 satin nickel | |
| • friction fit acrylic diffuser | 2-6135 | 2 x 26W quad 4-pin fluorescent (G24q-3) | W = 14" dia. H = 4.5" | 24 satin nickel | |
| • twist fit glass diffuser | 2-6114 | 2 x 26W quad 4-pin fluorescent (G24q-3) | W = 14" dia. H = 4.5" | 24 satin nickel 30 satin brass 14 polished chrome 95 old world | |
| • twist fit glass diffuser | 2-6141 | 2 x 26W quad cfl (G24q-3) | W = 14" dia. H = 4.5" | 24 satin nickel | *EM integral emergency ballast (26141 series only) |
| • twist fit glass diffuser | 2-6136 | 1 x 22W + 40W T5 circline lamps (2GX13) | W = 21" dia. H = 4.75" | 24 satin nickel | |

general specifications

- Formed steel trim.
- Cold rolled steel housing.
- Glass diffusers are 1/8" white opal.
- Acrylic diffusers are 3/16" matte white (2-6135 only).
- All items U.L and C.U.L. approved for dry locations.
- 2-6134 series ballast is electronic HPF, rapid start, 120V. All others are electronic HPF, program start, universal voltage (120V to 277V).
- All units mount to 4" octagonal junction box. No additional supports required.
- Visit www.oxygenlighting.com for technical cut sheets.
- Oxygen reserves the right to modify designs at any time.
- * Unless otherwise specified, a Bodine ballast will be installed. Only EM ballasts that match an "F-can" hole pattern may be installed. If no EM battery is desired, order 2-6114 series.

sample catalog number

| | | | |
|-------------------------|---------------------|---------|------------------|
| series # | finish | options | catalog number |
| 2-6114 | 24 | | 2-6114-24 |
| journey series, 2 x 26W | satin nickel finish | none | |

